

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

December 18, 2018

Alex Bernal Regulatory Specialist I Buckman Laboratories, Inc. 1256 N. McLean Blvd Memphis, TN 38108

Subject: Label Amendment – Updating the Directions for Use

Product Name: Busan 1071 WB EPA Registration Number: 1448-376

Application Date: 05/22/2018 Decision Number: 541684

Dear Mr. Bernal:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Page 2 of 2 EPA Reg. No. 1448-376 Decision No. 541684

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, you may contact Aline Heffernan at 703-347-8602 or via email at heffernan.aline@epa.gov.

Sincerely,

Zeno Bain, Product Manager 33 Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs

Enclosure: Stamped Label

ACCEPTED

Dec 18, 2018

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 1448-376

Buckman

BUSAN® 1071 WB

| ACTIVE INGREDIENT(S) | |
|--------------------------------------|--------|
| 2-(Thiocyanomethylthio)benzothiazole | 2.5% |
| Methylene bis(thiocyanate) | 2.5% |
| OTHER INGREDIENTS | 95.0% |
| TOTAL | 100.0% |

DANGER PELIGRO

| FIRST AID | |
|------------------------|---|
| If in Eyes | Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice. |
| If on Skin, Clothes | Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control center or doctor for treatment advice. |
| If Swallowed | Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water, if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. |
| If Inhaled | Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice. |
| | HOT LINE NUMBER |

HOT LINE NUMBER

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact CHEMTREC at 1-703-741-5970 for emergency medical treatment information.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Causes skin burns. May be fatal if swallowed, inhaled, or absorbed through skin. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

PERSONAL PROTECTION EQUIPMENT:

Mixers, loaders, applicators, and other handlers must wear:

- Coveralls over long-sleeved shirt, long pants, socks, chemical-resistant footwear, and chemical resistant gloves (Barrier laminate, Butyl rubber, Nitrile rubber, Neoprene rubber, Polyvinyl Chloride, or Viton.
- Protective eyewear: goggles or face shield.
- Respirator with an organic-vapor removing cartridge with a prefilter approved for pesticide (MSHA/NIOSH approved number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P, or HE prefilter.

User Safety Recommendation: User should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. User should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing.

Handlers participating in hand-dip applications, including introduction of materials to and removal from the dip and handling materials still wet from the dip, must wear chemical-resistant full front aprons with attached full-sleeve gloves.

ENVIRONMENTAL HAZARDS: This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. **NOTE TO USER:** Do not apply this product in a way that will contact workers or other persons.

SAPSTAIN AND MOLD CONTROL: BUSAN 1071 WB is used to control sapstain and mold on freshly cut hardwood and softwood lumber, logs, poles, posts and timbers. It is applied by dipping or spraying the wood until complete surface wetting is accomplished. Use 5.6 to 44.0 kg of BUSAN 1071 WB/100 L water (12 to 96 lbs of BUSAN 1071 WB/100 gal water) and agitate vigorously until BUSAN 1071 WB is thoroughly dispersed. Rates to be used will vary according to temperature, humidity, wood moisture, storage conditions, etc. Under conditions suitable for aggressive mold growth, the high rate mentioned above should be used. Treatment should be made as quickly as possible after lumber is cut and always within 24 hours after cutting.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, BUSAN 1071 WB is added to the white water or stock at 0.4 to 2.0 lb/ton of dry paper or paperboard produced.

COOLING TOWERS: BUSAN 1071 WB is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting a dispersion containing 2.0 to 2.8% BUSAN 1071 WB in water onto the clean wood surfaces. The amount applied should provide 2.4 to 3.2 lb BUSAN 1071 WB per 1000 sq ft of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of BUSAN 1071 WB to the recirculating cooling water at the tower basin or cold well. The dosage should provide 5.0 lb of BUSAN 1071 WB per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after treatment. The shock treatment should be repeated every four months.

COOLING WATER: BUSAN 1071 WB is used to control algae, bacteria, and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 2.4 to 14.8 fl oz BUSAN 1071 WB per 1000 gal water in the system. Subsequent additions of 0.8 to 4.8 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, BUSAN 1071 WB is incorporated in the drilling fluid at concentrations of 0.2 to 1.0% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: BUSAN 1071 WB is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, waterdisposal systems, and other oil-field water systems at dosage rates of 15.6 to 52.0 fl oz of BUSAN 1071 WB per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. Continuous Feed Method: When system is noticeably fouled, add 15.6 to 52.0 fl oz BUSAN 1071 WB per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 15.6 to 52.0 fl oz BUSAN 1071 WB per 1000 gal of water continuously, or as needed to maintain control. Intermittent or Slug Method: When system is noticeably fouled, or to maintain control, add 15.6 to 52.0 fl oz BUSAN 1071 WB per 1000 gal of water for 4 to 8 hr per day and 1 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS: BUSAN 1071 WB is an oil-soluble preservative for the control of bacteria and fungi that cause the degradation of crude oil and refined fuel oils during storage. Crude and refined oils include, but are not limited to, olefinic, aromatic, paraffinic, and naphthenic oils. It should be added to the oil as it is being transferred from the shipping container to the storage tank at the rate of 2.4 to 24.0 fl oz BUSAN 1071 WB per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously to the suction side of the transfer pump.

HIDES AND SKINS: BUSAN 1071 WB is used to prevent bacterial decomposition of brine-cured hides and skins. BUSAN 1071 WB should be used at a level of 1.2 to 8.0 lb/1000 lb of green fleshed hides or skins. In raceway operations BUSAN 1071 WB can be added directly to the raceway during addition of hides and operation of paddles. In processor operations BUSAN 1071 WB should be added as a dispersion in water. A satisfactory dispersion of one part BUSAN 1071 WB plus four parts water can be prepared by adding the BUSAN 1071 WB to the water (as opposed to adding water to BUSAN 1071 WB) with agitation.

LEATHER: To prevent mold growth on chrome- or vegetable-tanned hides and skins during tanning or post-tanning operations prior to finishing, BUSAN 1071 WB is used at treatment rates of 2.0 to 10.0 lb/1000 lb of white weight stock. A dispersion as described above should be prepared and added to the pickling solution or the tanning liquor during the tanning operation or to the rinse water in a post-tanning refloat.

COATINGS (non-paint): BUSAN 1071 WB is used to control fungal growth on coatings. Use levels will vary from 2.0 to 36.0% based on the total weight of the formulation. The exact level will depend on the severity of contamination as well as the nature and amounts of other components of the formulation.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. Pesticide wastes are acutely hazardous. Wastes resulting from the use of the product, excess pesticide, spray mixture, or rinsate must be collected and disposed of at an approved disposal facility. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER HANDLING:

(Text for all nonrefillable containers)

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

{Liquid residue removal statement for nonrefillable containers with capacity of 5 gals or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Liquid residue removal statement for nonrefillable containers with capacity of >5 gals}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use of disposal. Repeat this procedure two more times.

(Text for all nonrefillable containers)

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

{Text for refillable containers}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

{For containers larger than 55 gallons}

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

{For containers 55 gallons and smaller}

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times. Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured By: Buckman Laboratories, Inc.

1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A. (901) 278-0330 or 1-800-282-5626

Product Weight: 8.3 lbs/gal 1.0 kg/L NET CONTENTS MARKED ON CONTAINER

HMIS/NPCA RATING
Health 3 Flammability 1 Reactivity 1

Revised: 07/20/2018